

Earth electrodes

Earth rods



Threaded copperbond earth rod

Part no.	Nominal diameter (")	Length (mm)	Thread 'B' UNC (")	Shank 'A' (mm)	Weight each (kg)
RB105	Ø½	1,200	⅝	12.7	1.18
RB110	Ø½	1,500	⅝	12.7	1.55
RB115	Ø½	1,800	⅝	12.7	1.76
RB125	Ø½	2,400	⅝	12.7	2.36
RB205-FU	Ø⅝	1,200	⅝	14.2	1.53
RB210	Ø⅝	1,500	⅝	14.2	1.88
RB215	Ø⅝	1,800	⅝	14.2	2.29
RB220-FU	Ø⅝	2,100	⅝	14.2	2.51
RB225	Ø⅝	2,400	⅝	14.2	3.00
RB235	Ø⅝	3,000	⅝	14.2	3.79
RB305	Ø¾	1,200	¾	17.2	2.19
RB310	Ø¾	1,500	¾	17.2	2.73
RB315	Ø¾	1,800	¾	17.2	3.27
RB320-FU	Ø¾	2,100	¾	17.2	3.83
RB325	Ø¾	2,400	¾	17.2	4.35
RB335	Ø¾	3,000	¾	17.2	5.44

– High tensile low carbon steel core with minimum 250 microns of copper

Fittings

Part no.	Type (")	Weight (kg)
CG170	½ Coupling	0.09
CG270	⅝ Coupling	0.08
CG370	¾ Coupling	0.13
ST100	½ Driving stud	0.05
ST200	⅝ Driving stud	0.08
ST300	¾ Driving stud	0.12

Standards

IEC/BS EN 62561-2
BS 7430



UL467 (RB125, RB225,
RB235, RB325, RB335,
CG270, CG370)

