


Clamping Piece Variants

For example as a connection with end piece for constructions or downpipe clamps.
Clamping piece with square hole 11 mm and truss head screw.

Part No.	390 150	390 157	390 159
Material of clamp	St/tZn	Cu	StSt
Clamping range Rd	6-10 mm	6-10 mm	6-10 mm
Screw	⬆ M10 x 35 mm	⬆ M10 x 35 mm	⬆ M10 x 35 mm
Material of screw / nut	St/tZn	StSt	StSt
Standard	EN 62561-1	EN 62561-1	EN 62561-1
PU	100 pc(s)	1 pc(s)	100 pc(s)




KS Connectors

Clamping screw connector (KlemmSchrauben-Verbinder) for lightning current carrying connection of round conductors, e.g. to flat profiles, downpipe clamps or other parts of the lightning protection system.


One-piece, St/tZn With screw and nut M10.

Part No.	301 000	301 010
Material of clamping screw	St/tZn	St/tZn
Material of clamp	ZDC	ZDC
Clamping range Rd	7-10 mm	7-10 mm
Type	—	+ spring washer
Standard	EN 62561-1	EN 62561-1
PU	100 pc(s)	100 pc(s)



One-piece, Cu With screw and nut M10.

Part No.	301 007	301 017
Material of clamping screw	Cu	Cu
Material of clamp	Gunmetal	Gunmetal
Clamping range Rd	6-10 mm	6-10 mm
Connection (single-wire / multi-wire)	25-70 mm ²	25-70 mm ²
Type	—	+ spring washer
Standard	EN 62561-1	EN 62561-1
PU	1 pc(s)	1 pc(s)



One-piece, StSt With screw and nut M10.

General technical data:	
Clamping range Rd	6-10 mm
Standard	EN 62561-1

Part No.	301 009	301 089	301 019
Material of clamping screw	StSt	StSt (V4A)	StSt
Material of clamp	StSt	StSt (V4A)	StSt
Connection (single-wire / multi-wire)	25-70 mm ²	25-70 mm ²	25-70 mm ²
Type	—	—	+ spring washer
PU	100 pc(s)	100 pc(s)	100 pc(s)



Part No.	301 099	540 122
Material of clamping screw	StSt (V4A)	StSt (V4A)
Material of clamp	StSt (V4A)	StSt (V4A)
Connection (single-wire / multi-wire)	25-70 mm ²	16-50 mm ²
Type	+ spring washer	+ spring washer
PU	100 pc(s)	25 pc(s)



Heavy design With screw and nut M12.

Part No.	300 002	300 017
Material of clamping screw	St/tZn	Cu
Material of clamp	MCI	Gunmetal
Clamping range Rd	8-12.5 mm	8-12.5 mm
Connection (single-wire / multi-wire)	50-95 mm ²	50-95 mm ²
Standard	EN 62561-1	EN 62561-1
PU	25 pc(s)	1 pc(s)

