

## Down Conductor – Conductor Holders



### Height 16 mm with screw

| Part No.                     | 204 006     |
|------------------------------|-------------|
| Thread of conductor holder   | M8          |
| Material of conductor holder | plastic     |
| Colour of conductor holder   | grey ●      |
| Conductor support Rd         | 8 mm        |
| Screw                        | ⚙ 5 x 50 mm |
| PU                           | 50 pc(s)    |



### Height 16 mm, pre-assembled with screw, cover plate and dowel

| Part No.                     | 204 120     |
|------------------------------|-------------|
| Thread of conductor holder   | M8          |
| Material of conductor holder | plastic     |
| Colour of conductor holder   | grey ●      |
| Conductor support Rd         | 8 mm        |
| Screw                        | ⚙ 5 x 50 mm |
| Plastic plug                 | Ø8 x 40 mm  |
| PU                           | 50 pc(s)    |

## Conductor Holders DEHNfix



Two-in-one system (fixes the holder and the conductor) with conductor holder DEHNquick, fixed conductor routing, UV-stabilised.

### Height 30 mm


| Part No.                   | 250 000    | 250 001    | 250 007    |
|----------------------------|------------|------------|------------|
| Material of clamp          | St/tZn     | StSt       | Cu         |
| Material of base part      | plastic    | plastic    | plastic    |
| Conductor support Rd       | 6-10 mm    | 6-10 mm    | 6-10 mm    |
| Colour of conductor holder | grey ●     | grey ●     | brown ●    |
| Nail plug                  | Ø8 x 80 mm | Ø8 x 80 mm | Ø8 x 80 mm |
| Drilling depth             | 45 mm      | 45 mm      | 45 mm      |
| PU                         | 50 pc(s)   | 50 pc(s)   | 50 pc(s)   |

**Note:** Only suitable for solid stone or concrete.

## Conductor Holders DEHNhold

Conductor holder with a slotted saddle clamp for fixing round conductors, fixed conductor routing.  
For use with different materials, e.g. Al, StSt, St/tZn and Cu.

### With female thread



| Part No.                     | 274 110    | 274 117       |
|------------------------------|------------|---------------|
| Material of conductor holder | StSt       | StSt / gal Cu |
| Conductor support Rd         | 8-10 mm    | 8-10 mm       |
| Conductor support Fl         | 20 mm      | 20 mm         |
| Height of conductor holder   | 20 mm      | 20 mm         |
| Thread of conductor holder   | M8         | M8            |
| Standard                     | EN 62561-4 | EN 62561-4    |
| PU                           | 50 pc(s)   | 50 pc(s)      |

### With female thread, pre-assembled with plastic base



| Part No.                     | 274 150    |
|------------------------------|------------|
| Material of conductor holder | StSt       |
| Conductor support Rd         | 8-10 mm    |
| Conductor support Fl         | 20 mm      |
| Height of conductor holder   | 20 mm      |
| Thread of conductor holder   | M8         |
| Standard                     | EN 62561-4 |
| PU                           | 50 pc(s)   |

## Down Conductor – Conductor Holders

With female thread, pre-assembled with screw, plastic base and plug

| Part No.                     | 274 160     | 274 167       |
|------------------------------|-------------|---------------|
| Material of conductor holder | StSt        | StSt / gal Cu |
| Conductor support Rd         | 8-10 mm     | 8-10 mm       |
| Conductor support Fl         | 20 mm       | 20 mm         |
| Height of conductor holder   | 20 mm       | 20 mm         |
| Thread of conductor holder   | M8          | M8            |
| Plastic base                 | grey ●      | brown ●       |
| Screw                        | ⌈ 5 x 50 mm | ⌈ 5 x 50 mm   |
| Standard                     | EN 62561-4  | EN 62561-4    |
| PU                           | 50 pc(s)    | 50 pc(s)      |



With female thread, e.g. for round wire with plastic sheath

| Part No.                     | 274 113  |
|------------------------------|----------|
| Material of conductor holder | StSt     |
| Conductor support Rd         | 13 mm    |
| Height of conductor holder   | 20 mm    |
| Thread of conductor holder   | M8       |
| PU                           | 50 pc(s) |



## Conductor Holder with Saddle Clamp – Flat Design

Two-screw clamp with two M6 screws, for round and flat conductors.  
With plastic cover disc (grey).

Pre-assembled with wood screw, plastic cover disc (grey) and plug

| Part No.                     | 286 819     |
|------------------------------|-------------|
| Conductor support Rd         | 7-10 mm     |
| Conductor support Fl         | 30 mm       |
| Height of conductor holder   | 10 mm       |
| Material of conductor holder | StSt        |
| Screw                        | ⌈ 5 x 50 mm |
| Plastic plug                 | Ø8 x 40 mm  |
| Standard                     | EN 62561-4  |
| PU                           | 50 pc(s)    |



## Conductor Holders with Saddle Clamp and Flange

Complete unit with flange for installing conductors, fixed conductor routing.

With M8 female thread

| Part No.                   | 275 110    |
|----------------------------|------------|
| Conductor support Rd       | 7-10 mm    |
| Thread of conductor holder | M8         |
| Height of conductor holder | 20 mm      |
| Material of clamp          | St/tZn     |
| Material of base part      | ZDC        |
| Standard                   | EN 62561-4 |
| PU                         | 50 pc(s)   |



With female thread, pre-assembled with screw and plug

| Part No.                   | 275 160     |
|----------------------------|-------------|
| Conductor support Rd       | 7-10 mm     |
| Thread of conductor holder | M8          |
| Height of conductor holder | 20 mm       |
| Material of clamp          | St/tZn      |
| Material of base part      | ZDC         |
| Screw                      | ⌈ 5 x 50 mm |
| Plastic plug               | Ø8 x 40 mm  |
| Standard                   | EN 62561-4  |
| PU                         | 50 pc(s)    |

