



Conductor Holders for Downpipes

For installing down conductors on downpipes with fixed conductor routing. All types are also suitable for plastic downpipes.

Type PPS With worm gear.

Part No.	200 079	200 077	200 089	200 087
Clamping range Ø pipe	80-100 mm	80-100 mm	100-120 mm	100-120 mm
Conductor support Rd	8 mm	8 mm	8 mm	8 mm
Material of conductor holder	StSt	StSt / gal Cu	StSt	StSt / gal Cu
PU	50 pc(s)	50 pc(s)	50 pc(s)	50 pc(s)

Type PS Screwless, pre-punched for tongs.

Part No.	200 069	200 067	200 059	200 057
Clamping range Ø pipe	80-120 mm, in steps of 5 mm	80-120 mm, in steps of 5 mm	100 mm	100 mm
Conductor support Rd	8 mm	8 mm	8 mm	8 mm
Material of conductor holder	StSt	Cu	StSt	Cu
PU	25 pc(s)	25 pc(s)	25 pc(s)	25 pc(s)

Type PV Adjustable, with clamping screw M8.

Part No.	200 029	200 039	200 027
Clamping range Ø pipe	50-120 mm	50-150 mm	50 -120 mm
Conductor support Rd	6-8 mm	6-8 mm	6-8 mm
Material of conductor holder	StSt	StSt	Cu/bronze
PU	10 pc(s)	10 pc(s)	10 pc(s)

Downpipe Clamps

Pipe clamps for connecting downpipes to the lightning equipotential bonding according to IEC/EN 62305-3.

Connection possibilities for Rd, e.g. with KS connector (Part No. 301 000) or with clamping piece (Part No. 390 150) (according to material).

For fixed pipe diameters

Part No.	420 100	420 120	420 107	420 127
Material	St/tZn	St/tZn	Cu	Cu
Clamping range pipe Ø	100 mm	120 mm	100 mm	120 mm
Hole Ø	11 mm	11 mm	11 mm	11 mm
Standard	EN 62561-1	EN 62561-1	EN 62561-1	EN 62561-1
PU	50 pc(s)	1 pc(s)	1 pc(s)	1 pc(s)

Bimetallic type

For connecting St conductors with Cu downpipes, with St/tZn clamping piece and intermediate plate (Cupal).

Part No.	420 207
Material	Cu / St/tZn
Clamping range pipe Ø	100 mm
Clamping range Rd	6-10 mm
Standard	EN 62561-1
PU	1 pc(s)

Type RV, adjustable

With additional anti-rotation locking of the fixing screw and markings, predetermined bending points as well as pre-punched cutting aids.

General technical data:				
Hole Ø	10.5 mm			
Standard	EN 62561-1			
Part No.	423 010	423 011	423 017	423 019
Material	St/tZn	Al	Cu	StSt
Clamping range pipe Ø	60-100 mm	60-100 mm	60-100 mm	60-100 mm
Length	337 mm	337 mm	337 mm	337 mm
PU	50 pc(s)	50 pc(s)	1 pc(s)	50 pc(s)
Part No.	423 020	423 021	423 027	423 029
Material	St/tZn	Al	Cu	StSt
Clamping range pipe Ø	60-150 mm	60-150 mm	60-150 mm	60-150 mm
Length	494 mm	494 mm	494 mm	494 mm
PU	50 pc(s)	50 pc(s)	50 pc(s)	50 pc(s)