

Earth Entry Rod Set

Complete with disconnecting sleeve and connection clamps (KS screws).

Type St/tZn

With disconnecting sleeve (Part No. 450 000) and KS screws (Part No. 300 000).


Part No.	480 150
Material	St/tZn
Standard	EN 62561-(1+2)
Length	1500 mm
Connection KS screw Rd	7-10 mm
Connection sleeve Rd / Rd	7-10 / 16 mm
PU	1 pc(s)



Type Cu

With disconnecting sleeve (Part No. 450 007) and KS screws (Part No. 300 007).

Part No.	480 157
Material	Cu
Standard	EN 62561-(1+2)
Length	1500 mm
Connection KS screw Rd	6-10 mm
Connection sleeve Rd / Rd	7-10 / 16 mm
PU	1 pc(s)



Earth Entry Rods

For connecting down conductors to the earth-termination system.

Chamfered

General technical data:			
Standard	EN 62561-2		
Diameter Ø	16 mm		
Part No.	483 150	483 200	104 903
Material	St/tZn	St/tZn	StSt (V4A)
Material No.	—	—	1.4571 / 1.4404 / 1.4401
ASTM / AISI:	—	—	316Ti / 316L / 316
Length	1500 mm	2000 mm	1000 mm
PU	10 pc(s)	10 pc(s)	10 pc(s)
Part No.	104 905	104 906	
Material	StSt (V4A)	StSt (V4A)	
Material No.	1.4571 / 1.4404 / 1.4401	1.4571 / 1.4404 / 1.4401	
ASTM / AISI:	316Ti / 316L / 316	316Ti / 316L / 316	
Length	1500 mm	2000 mm	
PU	10 pc(s)	10 pc(s)	



With forged flat lug

Hole Ø11 mm, hole distance 22 mm.

Part No.	101 150
Material	St/tZn
Standard	EN 62561-2
Diameter Ø	16 mm
Length	1500 mm
Hole distance	22 mm
PU	10 pc(s)



Tapered

Notched conductor Ø10 mm, partly insulated (length approx. 700 mm).

Part No.	480 018	480 019	480 020	480 021
Material	St/tZn	St/tZn	St/tZn	St/tZn
Standard	EN 62561-2	EN 62561-2	EN 62561-2	EN 62561-2
Diameter Ø	16 / 10 mm	16 / 10 mm	16 / 10 mm	16 / 10 mm
Total length	1500 mm	1750 mm	2000 mm	2500 mm
Partial length Ø16 mm	1000 mm	750 mm	1000 mm	1500 mm
Partial length Ø10 mm	500 mm	1000 mm	1000 mm	1000 mm
PU	10 pc(s)	10 pc(s)	10 pc(s)	10 pc(s)

