

Rigid Straps

Snap-On Type One Hole - Steel



Features

- Inverted rib for strength
- Easy to install

Applications


- Indoor or outdoor use
- Use to secure Rigid or IMC conduit to wood, masonry or where greater load bearing is required

Standard Material

- Steel

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
C-RS1050	½"	50	500	21	1.910	0.870
C-RS1075	¾"	50	500	15	2.260	1.060
C-RS1100	1"	25	250	25	2.560	1.300
C-RS1125	1-¼"	20	200	20	2.790	1.730
C-RS1150	1-½"	20	200	32	3.690	1.970
C-RS1200	2"	10	100	22	4.170	2.280
C-RS1250	2-¼"	—	50	21	4.970	2.910
C-RS1300	3"	—	25	13	5.650	3.350
C-RS1350	3-½"	—	25	18	6.300	4.130
C-RS1400	4"	—	25	20	6.890	4.370
C-RS1500	5"	—	10	5	9.000	1.500
C-RS1600	6"	—	10	6	10.350	1.500

Snap-On Type Two Hole - Steel



Features

- Greater load bearing capability
- Easy to install

Applications

- Indoor or outdoor use
- Use to secure Rigid or IMC conduit to wood, masonry or where greater load bearing is required

Standard Material

- Steel

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
C-RS2050	½"	50	500	13	2.520	0.870
C-RS2075	¾"	50	500	16	2.910	1.060
C-RS2100	1"	25	250	12	3.230	1.300
C-RS2125	1-¼"	20	200	13	4.410	1.750
C-RS2150	1-½"	10	100	12	4.490	1.970
C-RS2200	2"	—	50	7	5.200	2.280
C-RS2250	2-¼"	—	25	6	6.060	2.910
C-RS2300	3"	—	25	7	6.750	3.580
C-RS2350	3-½"	—	25	8	7.480	4.060
C-RS2400	4"	—	25	7	8.270	4.570
C-RS2500	5"	—	10	5	10.600	1.250
C-RS2600	6"	—	10	6	11.850	1.250