Product datasheet

Specifications





13A 250V 1Gang swithitched socket with Neon

E8215N

Main

Range	Pieno
Product Or Component Type	Socket-outlet
Device Application	Power supply
Switch Function	Switch
Rated Current	13 A at 250 V AC 50 Hz
Local Signalling	Neon
Number Of Gangs	1 gang
Load Type	No inductive load

Complementary

Minimum Develop Maxwelling	
Wiring Device Mounting	Flush
	Surface
Outlet Poles Configuration	2P + E china
Material	Polycarbonate: surround
	Polycarbonate: grid plate
Connections - Terminals	Switch: pillar terminals
	Socket: clamp terminal
Clamping Connection Capacity	2 x 2.5 mm ² for solid cable(s)
Width	87 mm
Height	87 mm
Depth	8.8 mm

Environment

Ambient Air Temperature For Operation	-540 °C
Relative Humidity	095 %
Standards	GB 16915.1-2003 GB 2099.1-2008

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	8.7 cm
Package 1 Length	0.88 cm

Package 1 Weight

0.001 g

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations