



Pieno - 16A 250V - 3 gang 1 way switch with fluorescent locator (WG)

E8233L1F_WG

Main

Range Of Produc	Pieno
Product Or Component Type	Switch
Switch Function	1-way
Switch Application	Switch
Rated Current	16 AX at 250 V AC 50 Hz
Local Signalling	Fluorescent (white)
Number Of Gangs	3 gangs
Load Type	Fluorescent Resistive

Complementary

Wiring Device Mounting	Flush Surface
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - Terminals	Pillar terminals
Clamping Connection Capacity	2 x 1.5 mm² for stranded cable(s) 2 x 2.5 mm² for solid cable(s)
Width	87 mm
Height	87 mm

Environment

Ambient Air Temperature For Operation	-540 °C
Relative Humidity	095 %
Standards	GB 16915.1 IEC 60669-1
Product Certifications	CCC

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.426 cm
Package 1 Width	8.723 cm
Package 1 Length	8.685 cm

Package 1 Weight	93.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	10.7 cm
Package 2 Width	18.6 cm
Package 2 Length	19.7 cm
Package 2 Weight	1.032 kg
Unit Type Of Package 3	CAR
Number Of Units In Package 3	60
Package 3 Height	23.1 cm
Package 3 Width	29.5 cm
Package 3 Length	39.6 cm
Package 3 Weight	6.659 kg



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations