

Safety switch, general duty, fusible, 200A, 3 pole, 60hp, 240VAC, NEMA 3R, 4 wire, 1 neutral, bolt on hub provision

D324NRB

Main

Product	Single Throw Safety Switch
Duty Rating	General duty
Device Application	Residential
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phases
Number Of Poles	3
Current Rating	200 A
Voltage Rating	240 V AC
Enclosure Rating Nema	NEMA 3R
Motor Power Hp	15 hp at 240 V AC 60 Hz for 1 phase motors 25 hp at 240 V AC 60 Hz for 3 phases motors 60 hp at 240 V AC 60 Hz for 3 phases motors

Complementary

Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R
Fuse Type	H, K or R
Mounting Type	Surface
Electrical Connection	Lugs
Wiring Configuration	4-wire (3P + E)
Wire Size	AWG 6250 kcmil aluminium/copper
Tightening Torque	31.07 N.m (AWG 6250 kcmil)
Depth	215.90 mm
Width	482.60 mm
Height	742.95 mm
Net Weight	25.63 kg

Environment

Certifications UL listed file E2875

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	21.336 cm
Package 1 Width	49.022 cm
Package 1 Length	78.232 cm
Package 1 Weight	20.253 kg
Unit Type Of Package 2	PAL
Number Of Units In Package 2	15
Package 2 Height	114.3 cm
Package 2 Width	101.6 cm
Package 2 Length	121.92 cm
Package 2 Weight	318.875 kg

Contractual warranty

Warranty 18 months

Sustainability

Green Premium[™] label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Pvc Free	
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
Eu Rohs Directive	Compliant EU RoHS Declaration