Product datasheet

Specifications





Safety switch, general duty, non fusible, 100A, 3 pole, 30hp, 240VAC, NEMA 1

DU323

Main

Product	Single Throw Safety Switch
Duty Rating	General duty
Device Application	Residential
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Phase	3 phases
Number Of Poles	3
Current Rating	100 A
Voltage Rating	240 V AC
Enclosure Rating Nema	NEMA 1
Motor Power Hp	15 hp at 240 V AC 60 Hz for 1 phase motors 30 hp at 240 V AC 60 Hz for 3 phases motors

Complementary

Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring Configuration	3-wire	
Wire Size	AWG 14AWG 1 copper AWG 12AWG 1 aluminium	
Tightening Torque	3.95 N.m for 2.085.26 mm² (AWG 14AWG 10) 3.95 N.m (AWG 14AWG 10) 4.52 N.m for 8.37 mm² (AWG 8) 5.08 N.m for 12.321.12 mm² (AWG 6AWG 4) 5.65 N.m (AWG 3AWG 1)	
Depth	165.10 mm	
Width	266.70 mm	
Height	444.50 mm	
Net Weight	7 kg	

Environment

Certifications

UL listed file E2875

PCE

1

Packing Units

Unit Type Of Package 1

Number Of Units In Package 1

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	18.288 cm
Package 1 Width	27.432 cm
Package 1 Length	50.292 cm
Package 1 Weight	6.35 kg
Unit Type Of Package 2	PAL
Number Of Units In Package 2	40
Package 2 Height	99.06 cm
Package 2 Width	101.6 cm
Package 2 Length	121.92 cm
Package 2 Weight	271.248 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Technical illustration

Wiring diagram

NOT FUSIBLE



DU323