# **Product datasheet**

Specifications





# Socket, Vivace, 13A, 250V, 2 gangs, white

KBT426

#### Main

| Range                     | Vivace             |  |
|---------------------------|--------------------|--|
| Product Or Component Type | Socket-outlet      |  |
| Device Short Name         | KB426              |  |
| Device Application        | Power supply       |  |
| Device Presentation       | Complete mechanism |  |
| Outlet Standard           | British            |  |
| Colour Tint               | White              |  |
| Type Of Packing           | Plastic bag        |  |
| Socket Number             | 2                  |  |
| Rated Current             | irrent 13 A        |  |
| Colour Tint               | Wall: white        |  |

### Complementary

| •                              |   |  |
|--------------------------------|---|--|
| Integrated Connection Type     | 2 socket-outlet 220250 V AC, maximum load current: 13 A             |  |
| Outlet Standard                | British   |  |
| Outlet Standard Description    | Flat pin  |  |
| Outlet Poles Configuration     | 2 x 2P + E with shutters  |  |
| Number Of Gangs                | 2 gangs   |  |
| Material                       | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Nylon: base |  |
| Projecting Depth               | 8 mm  |  |
| Device Mounting                | Flush   |  |
| Mounting Support               | Wall mounted  |  |
| Fixing Mode                    | By screws   |  |
| Fixing Center                  | 120.6 mm  |  |
| Embedding Depth                | 20 mm   |  |
| Rated Current                  | 13 A at 250 V AC, resistive   |  |
| [Ue] Rated Operational Voltage | <b>Voltage</b> 220240 ∨   |  |
| Network Frequency              | 50/60 Hz  |  |
| Network Type                   | AC  |  |
| Contacts Material              | Brass and phosphor bronze   |  |

| Connections - Terminals      | Screw terminals                                   |  |
|------------------------------|---|--|
| Terminal Identifier          | L<br>N  |  |
| Tightening Torque            | 0.4 N.m   |  |
| Clamping Connection Capacity | 2.5 mm <sup>2</sup><br>4 mm <sup>2</sup>          |  |
| Width                        | 146 mm  |  |
| Surface Treatment            | Untreated   |  |
| Height                       | 86 mm   |  |
| Surface Finish               | Glossy  |  |
| Depth                        | 28 mm   |  |
| Number Of Terminals          | 3   |  |
| Clamping Connection Capacity | 1 x 2.53 x 2.5 mm² for rigid or stranded cable(s) |  |

#### **Environment**

| Standards                             | BS 1363-2<br>SS 145<br>MS 589 |
|---------------------------------------|-------------------------------|
| Ambient Air Temperature For Operation | -540 °C                       |
| Ambient Air Temperature For Storage   | -560 °C                       |
| Relative Humidity                     | 095 %                         |
| Operating Altitude                    | 02000 m                       |
| Environmental Characteristic          | Indoor use                    |
| Ip Degree Of Protection               | IP20                          |

## **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Weight             | 168.5 a |

#### **Contractual warranty**

Warranty 18 months



Green Premium<sup>TM</sup> label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

| <b>Ø</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>⊘</b> | Toxic Heavy Metal Free     |     |
| <b>Ø</b> | Mercury Free               |     |
| <b>⊘</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |